



Side Discharge Inverter Condensing Unit

Unidad de condensación de inversor de descarga lateral

MODEL / MODELO: CRSVT_AS

SPECIFICATIONS / ESPECIFICACIONES

Model name		CRSVT36AS	CRSVT48AS	CRSVT60AS	
Power supply	V/Ph/Hz	208~230-1-60	208~230-1-60	208~230-1-60	
Input consumption	W	600-4000	600-5000	600-6000	
Current	A	2.5-18	2.5-24	2.5-30	
Cooling	Capacity	BTU/H	340000	46000	56500
	SEER		15	15	14.5
	EER	BTU/H/W	10.3	10.3	10.1
Outdoor coil	Number of row		2	3	2
	Fin spacing	mm	1.6	1.6	1.6
	Fin material		Hydrophilic Aluminum	Hydrophilic Aluminum	Hydrophilic Aluminum
	Tube outside diameter	mm	Φ9.52	Φ7	Φ9.52
	Tube material		Inner grooved	Inner grooved	Inner grooved
	Coil length x height x width	mm	1000x750x43	874x945x40.1	794x1276x38.1
	Number of circuit		4	7	7
Compressor	Brand		Mitsubishi	GMCC	Mitsubishi
	Model		TNB220FFEMC	DA250S2C-30MT	MNB40FEQMC
	Type		Twin-rotary	Twin-rotary	Twin-rotary
	Capacity	W/h	6940	7690	12900
	Input	W	2150	2120	3960
	Rated current(RLA)	A	8.7	8.85	14.8
	Refrigerant oil	ml	520	1000	1100
Outdoor fan motor	Brand		Chigo	Chigo	Kaibang
	Qty		1	1	2
	Model		YDK-150-6CH F	YDK-200-8CF	YDK-60-6P2
	Input	W	300	400	190
	Running current	A	/	/	/
	Capacitor	μF	5	10	5
	Speed	r/min	800	800	830
Outdoor air flow	m ³ /h	4500	5000	6000	
Outdoor noise level	dB(A)	57	60	60	
Outdoor dimension	Unit (WxDxH)	mm	968x432x744	1054x399x994	902x392x1293.2
	Packing (WxDxH)	mm	1120x485x900	1145x475x1120	964x402x1445
Net/Gross weight	kg	66/71	81/91	95/103	

- Manufacturer reserves the right to change, at any time, specifications and designs without notice and without obligations.

- El fabricante se reserva el derecho de realizar cambios a las especificaciones y diseños en cualquier momento, sin previo aviso y obligaciones