



# SPECIFICATION : MODEL EFSFT

MODEL		36	60	90	120
Cooling Capacity	BTU/hr	34,000	56,000	84,000	112,000
	kW	9.9	16.4	24.6	32.8
Heating (optional)	BTU/hr	36,000	60,000	90,000	120,000
	kW	10.5	17.5	26.3	35.1
Air Flow	cfm	1400	1800	3000	3000
	m <sup>3</sup> /hr	2380	3060	5100	5100
Coil	Area sq. ft.	4.0	4.7	9.0	9.0
	rows	2	3	2	3
Blower	qty	1	1	2	2
	W x φ mm	180 x 378	180 x 378	180 x 378	180 x 378
Sound Level	dB(A)	54	54	57	57
Power Supply	V-Ph-Hz	220/240-1-50			
Fan motor	qty	1	1	2	2
	HP	1/2	1/2	1/2	1/2
	RLA	1.9	1.9	3.8	3.8
	Watt	235	235	470	470
Connection	liquid in	1/2	1/2	1/2	5/8
	suction in	3/4	3/4	1-3/8	1-3/8
	drain in	3/4	3/4	3/4	3/4
Unit Dimensions	Width mm	590	840	1090	1090
	Depth mm	380	380	380	380
	Height mm	1900	1900	1900	1900
NW/ GW	kg	80 / 90	90 / 100	170 / 190	180 / 200

- Digital Electronic Controller
- Wireless IR Remote control
- Air Swing
- Sturdy steel cabinet
- High Air flow for rapid climate control
- Quiet Operation
- Removable and Washable filters
- High efficiency multi speed PSC motor with internal thermal protection
- Cool only or Heat/Cool (optional)

