



Kora Inverter Series

Serie Kora Inverter

MODEL / MODELO: HWDKT / HRDKT

SPECIFICATIONS / ESPECIFICACIONES

Model		HWDKT30/HRDKT30		HWDKT36/HRDKT36	
Power Supply		V-Ph-Hz	208V~230V,60Hz		208V~230V,60Hz
Cooling	Capacity	Btu/h	30000		36000
	Rated current	W	2900		3300
	SEER	Btu/w	18.8		17.6
	Minimum Circuit Ampacity	A	1.55		1.75
	Max Fuse	A	30		30
Heating	Capacity	Btu/h	31000		33500
	Rated current	W	2700		3100
	HSPF		12.3		9.6
Compressor	Type		Rotary		Rotary
	Brand		Hitachi		Hitachi
Minimum Circuit Ampacity		A	1.55		1.75
Max Fuse		A	30		30
Indoor air flow		m3/h	1800		1800
Indoor noise level (Hi/Mi/Lo/silence)		dB(A)	50/45/40/38		50/45/40/38
Outdoor noise level			60		60
Indoor unit	Dimension(W*D*H)	mm	1280x360x260		1280x360x260
	Dimension(W*D*H)	inch	50 3/8x14 3/16x10 1/4		50 3/8x14 3/16x10 1/4
	Packing (W*D*H)	mm	1385x435x325		1385x435x325
	Packing (W*D*H)	inch	54 1/2x17 1/8x12 13/16		54 1/2x17 1/8x12 13/16
	Net/Gross weight	Kg	18.0 / 21.5		19.5 / 23.0
	Net/Gross weight	lbs.	39.6 / 47.3		42.9 / 50.7
Outdoor unit	Dimension(W*D*H)	mm	885x795x366		885x795x366
	Dimension(W*D*H)	inch	34 7/8x31 5/16x14 3/8		34 7/8x31 5/16x14 3/8
	Packing (W*D*H)	mm	1050x890x500		1050x890x500
	Packing (W*D*H)	inch	41 11/32x35x19 11/16		41 11/32x35x19 11/16
	Net/Gross weight	Kg	58 / 63		60 / 65
	Net/Gross weight	lbs.	72.7 / 79.3		97 / 105
Refrigerant piping	Liquid side / Gas side	inch	3/8" / 5/8"		3/8" / 5/8"
Refrigerant			R410A		R410A
Refrigerant charge volume		g	2070		2250

Features and Benefits

➤ **Ultra Quiet**
Room Temperature

➤ **High Efficiency & Energy saving**
Cooling (°C / °F)

➤ **Fast Cooling**
15°C-46°C (5°F-115°F)

➤ **Self-Diagnosis & Automatic Protection**
(5°F-115°F)

