



DOE~Approved Window Unit

Unidad de ventana aprobado por DOE

MODEL / MODELO: MWDUT06BRJ SPECIFICATIONS / ESPECIFICACIONES

Model		MWDUT06BRJ	
Power supply		Ph-V-Hz	115V, 1PH
Cooling	RATED Capacity	Btu/h	6000
	RATED EER		3.58
	RATED Input	W	490
	RATED Current	A	4.5
	Standby power	W	0.9
Moisture Removal		L/h	0
Max. input consumption		W	700
Max. current		A	6.5
Starting current		A	19.5
Compressor	Model		ASN52E2VAZ3
	Type		Rotary
	Brand		GMCC
Refrigerant type (R410A)		oz	0.38
Design pressure		psi	300
Fan motor	Model		YKTS-50-4-53L
	Input	W	80.0
	Capacitor	uF	6
	Speed (H/M/L)	r/min	1490/1320/1220
Evaporator	Fin type (code)		Hydrophilic aluminium
	Tube outside dia.and type	mm	Φ7.94, Innergroove tube
	Coil length x height x width	mm	480×308×57.15
	Number of circuits		4
Indoor air flow (H/M/L)		ft3/min	0/0/329
Indoor noise level (H/M/L)		dB(A)	0/0/0
Condenser	Fin type (code)		Non-hydrophilic aluminium
	Tube outside dia.and type	mm	Innergroove tube
	Coil length x height x width	mm	320X210X40.1
	Number of circuits		2
Outdoor air flow (H/M/L)		ft3/min	0/0/0
Outdoor noise level (H/M/L)		dB(A)	0/0/63.1
Control type			Remote Control
Operation Temp	Indoor (cooling/heating)	°F	63°F-90°F
	Outdoor (cooling/heating)	°F	64°F-109°F
Application area (Cooling EPA)		sq.ft	86.11 – 129.17
Dimension (W*D*H)		in	18.54 x 15.75 x 13.39
Packing (W*D*H)		in	21.69 x 17.80 x 14.57
Net/Gross weight		lb	45.19/52.03